

**MANIFATTURA TUBI GOMMA s.p.a.**  
Grisignano di Zocco, 36040 (VI) ITALY  
T. +39 0444.614755 | info@mtgspa.com  
www.mtgspa.com



## APPLICATION

- Flexible connection hose in the discharge line of dredges, for hydraulic transport of sand, gravel and crushed materials.

## CONSTRUCTION

### TUBE

- NR/BR rubber, resistant to abrasion, smooth, black colour.
- Thickness: 15 mm.

### REINFORCEMENT

- High strength textile plies, divided by NR/SBR rubber.

### COVER

- Synthetic rubber, resistant to abrasion, ozone and weather. Black, smooth, cloth finish.

## FITTING

- Vulcanized stems or beaded rubber ends with trapezoidal cross-section.

## TEMPERATURE RANGE

- From -30°C to +70°C.

## WORKING PRESSURE

- 10 bar.

## SAFETY FACTOR

- $\geq 3$  times working pressure.

## NOTE

- It is only available in service lengths with couplings at the ends.
- The type of connections is to be agreed with our Technical Department.

## MARKING

- On demand.

## TECHNICAL SPECIFICATIONS

**SIZE TOLERANCES:** Inner diameter: ISO 1307 - Wall Thickness: DIN 7715 T4 S2 - Length: ISO 1307

For sizes and colours available, please contact our Sales Department.  
Above technical data refer to application at room temperature (+20°C).