

MANIFATTURA TUBI GOMMA S.p.A.

Grisignano di Zocco, 36040 (VI) ITALY
T. +39 0444.614755 | info@mtgspa.com
www.mtgspa.com



APPLICATION

- Flexible connection hose in the discharge line of dredges, for hydraulic transport of sand, gravel and crushed materials.

CONSTRUCTION

TUBE

- NR/BR rubber, resistant to abrasion, smooth, black colour.
- Thickness: 15 mm.

REINFORCEMENT

- High strength textile plies, divided by NR rubber.

COVER

- Synthetic rubber, resistant to abrasion, ozone and weather. Black, smooth, cloth finish.

FITTING

- Vulcanized stems or beaded rubber ends with trapezoidal cross-section.

TEMPERATURE RANGE

- From -30°C to +70°C.

WORKING PRESSURE

- 8 bar.

SAFETY FACTOR

- ≥ 3 times working pressure.

NOTE

- It is only available in service lengths with couplings at the ends.
- The type of connections is to be agreed with our Technical Department.

MARKING

- Upon request.

TECHNICAL SPECIFICATIONS

SIZE TOLERANCES: Inner diameter: ISO 1307 - Wall Thickness: DIN 7715 T4 S2 - Length: ISO 1307

For sizes and colours available, please contact our Sales Department.
Above technical data refer to application at room temperature (+20°C).