



**MANIFATTURA TUBI GOMMA S.p.A.**

 Grisignano di Zocco, 36040 (VI) ITALY  
 T. +39 0444.614755 | info@mtgspa.com  
 www.mtgspa.com


## APPLICATION

- Multipurpose delivery hose for conveying a wide range of aggressive chemicals.
- Normally installed on tank trucks and unloading platforms, recommended for applications in chemical laboratories and industries.

## CONSTRUCTION

### TUBE

- UPE (Ultra High Molecular Weight Polyethylene), neutral, smooth.
- Resistance: according to MTG Chemical Resistance Chart.

### REINFORCEMENT

- High strength plies of synthetic cord.
- Built-in copper wires.

### COVER

- EPDM rubber, black, smooth, antistatic ( $R < 10^6 \Omega$ ), resistant to abrasion, ageing and weather, cloth finish.

## TEMPERATURE RANGE

- From  $-35^\circ\text{C}$  to  $+100^\circ\text{C}$ .
- Resistant to steam up to  $+130^\circ\text{C}$  for max. 30 minutes.

## SAFETY FACTOR

- $\geq 3$  times working pressure.

## MARKING

# TECHNICAL SPECIFICATIONS

**SIZE TOLERANCES:** Inner diameter: ISO 1307 - Wall Thickness: DIN 7715 T4 S2 - Length: ISO 1307

Inner Diameter mm	Outer diameter mm	Wall thickness mm	Working pressure BAR	Burst pressure BAR	Vacuum BAR	Min. bending radius mm	Approx. weight kg/m	Max. length m
10	19	4.5	10	30	-0.60	60	0.24	40
13	22	4.5	10	30	-0.60	80	0.29	40
16	25	4.5	10	30	-0.50	100	0.34	40
19	30	5.5	10	30	-0.50	120	0.49	40
25	37	6.0	10	30	-0.50	150	0.66	40
30	42	6.0	10	30	-0.40	200	0.77	40
32	44	6.0	10	30	-0.30	200	0.81	40
35	48	6.5	10	30	-0.30	240	0.98	40
38	52	7.0	10	30	-0.30	240	1.05	40
40	54	7.0	10	30	-0.30	240	1.10	40
45	59	7.0	10	30	-0.20	280	1.21	40
50	65	7.5	10	30	-0.20	300	1.47	40
60	76	8.0	10	30	-	360	1.84	40
63.5	79.5	8.0	10	30	-	390*	1.93	40
75	91	8.0	10	30	-	450*	2.20	40
80	96	8.0	10	30	-	480*	2.30	40
90	106	8.0	10	30	-	540*	2.60	40
100	116	8.0	10	30	-	600*	2.82	40

 (\*) The bending radius can be reached at a pressure of  $\geq 1$  bar.

 Chemical resistance acc. to MTG Chemical Resistance Chart. Above technical data are based on application at room temperature ( $+20^\circ\text{C}$ ). Other sizes are available on request.