

MTG DRINKS







MANIFATTURA TUBI GOMMA S.D.A.

Grisignano di Zocco, 36040 (VI) ITALY T. +39 0444.614755 | info@mtgspa.com www.mtgspa.com



APPLICATION

- •Food grade hose designed for conveying high quality alcoholic beverages (such as beer, cider, wine and spirits with an alcohol content up to 50%) and soft drinks.
- ·Delivery hose.

CONSTRUCTION

TUBE

- •BIIR rubber (code 90FDA), light colour, food quality, odourless, tasteless, mirror smooth.
- •Compliance: Standard FDA, 3A, D.M. 21/03/73 and following amendments.

REINFORCEMENT

•Plies of synthetic cord.

•EPDM based rubber, red colour, resistant to abrasion and ozone,

SAFETY FACTOR

•≥ 3 times working pressure.

MAIN BENEFITS

- •The inner tube is totally free from plasticizers, phthalates and animal derived ingredients, thus reducing the risk of bacterial growth and contamination of the product conveyed.
- •The composition of the hose cover ensures excellent resistance to aging.
- •The hose complies with the Regulations EC 1935/2004 and 2023/2006/EC (GMP). The MTG production cycle is free from animal derived ingredients, phthalates, adipates and materials subject to restrictions according to the current European Regulation EC 1907/2006 (REACH).

TEMPERATURE RANGE

- •From -40°C to +120°C.
- •Sterilization up to +130°C for max. 30 minutes.

MARKING







TECHNICAL SPECIFICATIONS

SIZE TOLERANCES: I.D.: ISO 1307 - Wall thickness: DIN 7715 T4 S2 - Length: ISO 1307

lnner Diameter mm	Outer diameter mm	Wall thickness mm	Working pressure BAR	Burst pressure BAR	Vacuum BAR	Min. bending radius mm	Approx. weight kg/m	Max. length m
19	31	6	10	30	-0.6	120	0.52	40
25	37	6	10	30	-0.6	150	0.65	40
32	48	8	10	30	-0.6	190	1.10	40
38	56	9	10	30	-0.6	240	1.44	40
50	70	10	10	30	-0.5	350	2.07	40
65	87	11	10	30	-0.3	500	2.95	40
75	100	12.5	10	30	-0.3	600	3.80	40
100	130	15	10	30	-0.3	750	6.15	40

Other sizes and colours are available upon request. Please contact our Sales Department. Above technical data refer to application at room temperature (+20°C)













Cod. IT-M00003