

**MANIFATTURA TUBI GOMMA S.p.A.**  
Grisignano di Zocco, 36040 (VI) ITALY  
T. +39 0444.614755 | info@mtgspa.com  
www.mtgspa.com



## APPLICATION

- NBR rubber hose specifically engineered for application on peristaltic pumps.

## CONSTRUCTION

### TUBE

- NBR rubber, black colour, smooth.

### REINFORCEMENT

- Plies of synthetic cord.

### COVER

- NBR rubber, black colour, smooth, cloth finish.
- Version available with ground cover: MTG-PERISTALTIC/NBR/Ret.

## DIMENSIONS

- Normally supplied in service lengths.
- Inner diameter, wall thickness and length are defined by the peristaltic pump manufacturer.

## TEMPERATURE RANGE

- From -10°C to +90°C.

## WORKING PRESSURE

- 10 bar.

## SAFETY FACTOR

- $\geq 4$  times working pressure.

## NOTE

- For any further information concerning technical features, hose solutions available and chemical compatibility with the products conveyed, please contact MTG Sales Department.

## MARKING

- Without any marking or marking on demand.
- Without any marking for the version with ground cover.

## SIZE TOLERANCES

- Length and wall thickness: to be agreed with MTG Sales Department.