



MANIFATTURA TUBI GOMMA S.p.A.

Grisignano di Zocco, 36040 (VI) ITALY
T. +39 0444.614755 | info@mtgspa.com
www.mtgspa.com



APPLICATION

- NR rubber hose specifically engineered for application on peristaltic pumps.
- Suitable to convey liquid foodstuff.
- The hose complies with the Regulations EC 1935/2004 and 2023/2006/EC (GMP). The MTG production cycle is free from animal derived ingredients, phthalates, adipates and materials subject to restrictions according to the current European Regulation EC 1907/2006 (REACH).

CONSTRUCTION

TUBE

- NR rubber (code 112), light colour, mirror-smooth.
- Complying with FDA Standards, D.M. 21/03/73 and following amendments.

REINFORCEMENT

- Plies of synthetic cord.

COVER

- NR rubber, black colour, smooth, cloth finish.
- Version available with ground cover: MTG-PERISTALTIC/NR-Food/Ret.

DIMENSIONS

- Normally supplied in service lengths.
- Inner diameter, wall thickness and length are defined by the peristaltic pump manufacturer.

TEMPERATURE RANGE

- From -10°C to +80°C.

WORKING PRESSURE

- 10 bar.

SAFETY FACTOR

- ≥ 4 times working pressure.

NOTE

- For any further information concerning technical features, hose solutions available and chemical compatibility with the products conveyed, please contact MTG Sales Department.

MARKING

- Without any marking or marking on demand.
- Without any marking for the version with ground cover.

SIZE TOLERANCES

- Length and wall thickness: to be agreed with MTG Sales Department.

For sizes and colours available, please contact our Sales Department.
Above technical data refer to application at room temperature (+20°C).