

MANIFATTURA TUBI GOMMA S.p.A.
Grisignano di Zocco, 36040 (VI) ITALY
T. +39 0444.614755 | info@mtgspa.com
www.mtgspa.com



APPLICATION

- High quality rubber hose, perfect for handling beverages such as wine, fruit juice, beer, drinking water.
- Also suitable for milk and milk products.
- Suction and delivery hose.

CONSTRUCTION

TUBE

- EPDM rubber (code 140BI), light colour, odourless and tasteless, mirror-smooth.
- Compliance: FDA Standards, 3A, D.M. 21/03/73 and following amendments, BfR recommendations (Cat. II).

REINFORCEMENT

- Plies of synthetic cord.
- Embedded steel helix wire.

COVER

- Synthetic rubber, blue colour, smooth, abrasion and weather resistant, cloth finish.

SAFETY FACTOR

- ≥ 3 times working pressure.

MAIN BENEFITS

- The composition of the inner liner makes it highly resistant to acids and bases with medium concentration.
- Perfect solution for applications requiring an excellent temperature resistance.
- Alichem/SPL provides a high resistance to chemical cleaning and disinfection products used in food sanitation processes.
- Hose in accordance with EC 1935/2004 and 2023/2006/EC (GMP). The MTG production cycle is free from animal derived ingredients, phthalates, adipates and materials subject to restrictions acc. to EC 1907/2006 (REACH).

TEMPERATURE RANGE

- From -40°C to +120°C.

STERILIZATION

- Sterilization up to +140°C for max. 30 minutes.
- In case of long lasting sterilizations we suggest to use the model with vulcanized couplings at the ends.

MARKING


ALICHEM

MADE IN ITALY

TECHNICAL SPECIFICATIONS

SIZE TOLERANCES: I.D.: ISO 1307 - Wall thickness: DIN 7715 T4 S2 - Length: ISO 1307

Inner Diameter mm	Outer diameter mm	Wall thickness mm	Working pressure BAR	Burst pressure BAR	Vacuum BAR	Min. bending radius mm	Approx. weight kg/m	Max. length m
13	25	6.0	10	30	-0.9	50	0.46	40
16	28	6.0	10	30	-0.9	65	0.55	40
19	31	6.0	10	30	-0.9	80	0.62	40
25	37	6.0	10	30	-0.9	100	0.80	40
32	44	6.0	10	30	-0.9	130	0.99	40
38	51	6.5	10	30	-0.9	200	1.27	40
51	67	8.0	10	30	-0.9	250	2.15	40
63.5	79.5	8.0	10	30	-0.9	320	2.70	40
76	92	8.0	10	30	-0.9	450	3.10	40
102	120	9.0	10	30	-0.9	600	4.75	40

Other sizes and colours are available upon request. Please contact our Sales Department. Above technical data refer to application at room temperature (+20°C).

MTG reserves the rights to implement changes in product specifications without notice and as may be deemed appropriate by the Company for any technical or commercial reason.


Cod. IT-A00068

UPDATED: 12/24
Rev: 003