MTG-PERISTALTIC/EPDM

EN ISO 9001:2015
No. : Q-3353-24
EN ISO 45001:2018
No. : 20152240011742
EN ISO 14001:2015
No. : 20051240011741

MANIFATTURA TUBI GOMMA S.p.A.
Grisignano di Zocco, 36040 (VI) ITALY
T. +39 0444.614755 | info@mtgspa.com
www.mtgspa.com



APPLICATION

- EPDM rubber hose specifically engineered for application on peristaltic pumps.
- Excellent for conveying a wide range of chemicals* and corrosive liquids.

(*) Please contact the MTG Technical Sales Department to check the chemical compatibility with the products.

CONSTRUCTION

TUBE
- EPDM rubber, black colour, smooth.

REINFORCEMENT
- Plies of synthetic cord.

COVER
- EPDM rubber, black colour, smooth, cloth finish.
- Version available with ground cover: MTG-PERISTALTIC/EPDM/Ret.

DIMENSIONS

- Normally supplied in service lengths.
- Inner diameter, wall thickness and length are defined by the peristaltic pump manufacturer.

TEMPERATURE RANGE

- From -10°C to +100°C.

WORKING PRESSURE

- 10 bar.

SAFETY FACTOR

- ≥ 4 times working pressure.

NOTE

- For any further information concerning technical features, hose solutions available and chemical compatibility with the products conveyed, please contact MTG Sales Department.

MARKING

- Without any marking or marking on demand.
- Without any marking for the version with ground cover.

SIZE TOLERANCES

- Length and wall thickness: to be agreed with MTG Sales Department.

For sizes and colours available, please contact our Sales Department.
Above technical data refer to application at room temperature (+20°C).

Cod. IT-P00131

UPDATED: 04/18
Rev: 000