

MANIFATTURA TUBI GOMMA S.p.A.

Grisignano di Zocco, 36040 (VI) ITALY
T. +39 0444.614755 | info@mtgspa.com
www.mtgspa.com



APPLICATION

- Food hose specifically designed to meet the demanding requirements of the beer processing industry.
- It is suitable for conveying high quality raw, pasteurized and organic beer, alcoholic beverages, soft drinks and wine.
- Delivery and slight suction hose.

CONSTRUCTION

TUBE

- BIIR rubber (code 90FDA), light colour, food grade, odourless and tasteless, mirror smooth.
- It complies with FDA Standards, 3-A Sanitary Standards n.18-03-Class II, D.M. 21/03/73 and following amendments.
- Validation by the institute "Technische Universität München WEIHENSTEPHAN".

REINFORCEMENT

- Plies of synthetic cord.

COVER

- CR rubber, red colour, resistant to abrasion, ozone and weather, smooth, cloth finish.

MARKING

MAIN BENEFITS

- The very strong structure makes it perfect for loading and unloading operations in breweries.
- The composition of the cover ensures utmost resistance to aging.
- Hose in accordance with EC 1935/2004 and 2023/2006/EC (GMP).
- The MTG production cycle is free from animal derived ingredients, phthalates, adipates and materials subject to restrictions acc. to EC 1907/2006 (REACH).
- Non-plasticized hose.

SAFETY FACTOR

- ≥ 3 times working pressure.

TEMPERATURE RANGE

- From -40°C to +120°C depending on the product conveyed and on use.

STERILIZATION

- Sterilization up to +130°C for max. 30 minutes.
- In case of long lasting sterilizations we suggest to use the model with vulcanized couplings at the ends.

MTG BREWART

HOSE TESTED BY TECHNISCHE
UNIVERSITÄT MÜNCHEN WEIHENSTEPHAN



TECHNICAL SPECIFICATIONS

SIZE TOLERANCES: I.D.: ISO 1307 - Wall thickness: DIN 7715 T4 S2 - Length: ISO 1307

Inner Diameter mm	Outer diameter mm	Wall thickness mm	Working pressure BAR	Burst pressure BAR	Vacuum BAR	Min. bending radius mm	Approx. weight kg/m	Max. length m
13	23	5	16	48	-0.6	80	0.37	40
19	29	5	16	48	-0.6	120	0.48	40
25	37	6	16	48	-0.6	150	0.74	40
32	48	8	16	48	-0.6	200	1.38	40
38	56	9	16	48	-0.6	240	1.85	40
40	60	10	16	48	-0.6	240	2.10	40
50	70	10	16	48	-0.6	300	2.75	40
51	71	10	16	48	-0.6	300	2.80	40
63.5	87.5	12	16	48	-0.5	400	3.90	40
65	89	12	16	48	-0.5	400	4.00	40
75	105	15	16	48	-0.4	450	5.70	40
76	106	15	16	48	-0.4	450	5.75	40
80	110	15	16	48	-0.4	500	5.90	40
100	130	15	16	48	-0.4	600	6.95	40
102	132	15	16	48	-0.4	600	7.00	40

Other sizes and colours are available upon request. Please contact our Sales Department. Above technical data refer to application at room temperature (+20°C).



Cod. IT-B00038

UPDATED: 08/20
Rev: 001